









	Baby monitor with monitor					Baby monitor with app-enabled electronic nannies (WiFi)		
Model name	 Neno Gato 2	 Neno Vera	 Neno Berkano	 Neno Vista	 Neno Bambino	 Neno Lui	 Neno Avante	 Neno Ivo
Display	2 inches	3.2 inches	3.2 inches	5 inches	2.8 inches	×	×	5 inches
Display resolution	176×220 px	320×240 px	320×240 px	1280×720 px	320×240 px	×	×	1280×720 px
Adjustable camera viewing angle	×	×	YES	YES	×	×	YES	YES
Camera rotation angle	×	×	horizontal 300°; vertical 50°	horizontal 330°; vertical 135°	×	×	horizontal 355°; vertical 90°	horizontal 355°; vertical 110°
Two-way communication	YES	YES	YES	YES	YES	YES	YES	YES
App	×	×	×	×	×	Tuya Smart	Tuya Smart	Tuya Smart
VOX standby mode	YES	YES	YES	YES	YES	×	×	YES
Operating range	up to 260 m (outdoor), up to 50 m (indoor)	up to 260 m (outdoor), up to 50 m (indoor)	up to 260 m (outdoor), up to 50 m (indoor)	up to 300 m (outdoor), up to 50 m (indoor)	up to 300 m (outdoor), up to 50 m (indoor)	within WiFi range	within WiFi range	up to 500 m (outdoor), up to 100 m (indoor) and within WiFi range
Night mode (IR LEDs)	YES	YES	YES	YES	YES	YES	YES	YES
Built-in lullabies	Yes, 8 lullabies	Yes, 8 lullabies	Yes, 8 lullabies	Yes, 8 lullabies	Yes, 6 lullabies	Yes, 3 lullabies + white noise function	×	Yes, 8 lullabies
Motion detection	×	×	×	×	×	YES	YES	YES
Photo function	×	×	×	×	×	YES	YES	YES
Alarm function	YES	YES	YES	YES	YES	YES	YES	YES
Built-in night light	×	×	×	×	×	YES	×	×
Recording resolution	×	×	×	×	×	1080p (1920×1080)	1080p (1920×1080)	1080p (1920×1080)
MicroSD card support	×	×	×	×	×	max up to 32 GB	max up to 128 GB	max up to 128 GB
WiFi connectivity	×	×	×	×	×	WiFi.802.11 b/g/n 2.4 Ghz	WiFi.802.11 b/g/n 2.4 Ghz	WiFi.802.11 b/g/n 2.4 Ghz
Codec	×	×	×	×	×	H.264	H.264	H.264
Built-in rechargeable battery	750 mAh	1150 mAh	1150 mAh	3050 mAh	2600 mAh	×	×	3000 mAh
Operating temperature	-10~50°C	-10~50°C	-10~50°C	-10~45°C	-30~65°C	-10~50°C	-10~50°C	-30~65°C
Temperature monitoring	YES	YES	YES	YES	YES	YES	×	YES
Power supply	DC 5V 1A	DC 5V 1A	DC 5V 1A	DC 5V 1A	DC 5V 1A	DC 5V 1A	DC 5V 1A	DC 5V 1A
Zoom	×	3×	3×	3×	4×	×	×	4×
Dimensions	Receiver 62×126×24mm, Camera 62×110×60mm	Receiver 124×72×17mm, Camera 62×115×62mm	Receiver 124×72×17 mm Camera 116×72×66 mm	Receiver 162×86×22 mm Camera 71×71×116 mm	Receiver 119×80×37 mm Camera 65×65×106 mm	65×65×55mm (Camera), 120×80×50mm (case)	85×85×120 mm	Receiver 160×80×16mm Camera 82×85×119 mm
Weight	Receiver 94 g, Camera 67 g	Receiver 110 g, Camera 81 g	Receiver 123 g, Camera 179 g	Receiver 200 g, Camera 190 g	Receiver 125 g, Camera 93 g	76 g (Camera), 189 g (Camera in silicone case)	222 g	Receiver 171 g, Camera 220 g
Included	Camera, receiver, AC adaptor×2, user manual	Camera, receiver, AC adaptor×2, user manual	Camera, receiver, AC adaptor×2, user manual	Camera, receiver, AC adaptor×2, flexible handle, wall mounting kit, user manual	Camera, receiver, AC adaptor×2, flexible handle, user manual	Camera, silicone case, flexible handle, AC adaptor +USB cable, user manual	Camera, AC adaptor, USB cable, user manual	Camera, receiver, AC adaptor×2, flexible handle, wall mounting kit, user manual