Meno-NC1

fast wall charger

35W

















neno





Safety

The Neno NC1 was created with high-quality components, so it provides protection against overcharging, overloading/short-circuiting and overheating. This means you can charge your equipment without worrying about it getting damaged.

Protection against overload/short-circuit protection

(7)

Protection against overcharging

Protection against overheating











Input voltage: AC 100-240V 50/60Hz, 1.2A Max

Output voltage: USB-C(PD35W): 5V/3A, 9V/3A, 12V/2.91A,

15V/2.33A, 20V/1.75A,

USB-A(QC30W): 5V/3A, 9V/3A, 12V/2.5A,

20V/1.5A,

USB-A+USB-C: 5V/3.4A (17W Max),

PPS: (3.3V-11V/3A)

Total output power: 35W (Max)

Plug: EU

Technology: GaN3

 Supported protocols:
 PD3.0, PD2.0, QC2.0, QC3.0, QC4, QC4+,

 PD2.0, PE1.0, AFC, FCP, PPS, APPLE 2.4, BC1.2

Protections: Against overcharge, overload/short circuit,

overheating

Contents: Fast wall charger, User manual.

Dimensions: 80×40×32mm

Net weight: 65g

Box dimensions: 114×77×40mm

Gross weight: 108g

Product number: NEN-DOM-ŁS001

EAN code: 5902479675176

If you don't know which product to choose, need help, support or have questions for our midwives, neno lactation experts, call or email the neno Customer Support Centre directly.

Hotline 731 594 301 mail:info@neno.pl

